



SWISSTEC Sourcing Ltd.



Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.

Document No.: KKM011712-136

Item No: 500978420

Screw description:

DRS TRIM HD PH2 REVERSE COARSE FULL THRD WZP CR3 C1022
3.8X35

Material: C1022

Certificate No.: [J-32-20199-18](#)

Report No.: [32-9996/2](#)

| Size | Nominal diameter (mm) | Inner thread diameter (mm) | Head diameter (mm) | Total length (mm) | Thread length (mm) | Tensile strength in bending (15°) | Withdrawal strength (N) | Headpull-through strength (N) | Drilling ability | Protective layer (µm) |
|--------|--------------------------|-------------------------------|-----------------------|----------------------|-----------------------|--------------------------------------|----------------------------|----------------------------------|------------------|--------------------------|
| 3.8x35 | 3.6 - 3.9 | 2.35 - 2.65 | 6.5 - 7.0 | 33.7 - 36.3 | Full | Pass | 810 - 958 | 290 - 350 | Pass | Min 10.6 |

The manufacturer declares for:

The product is in accordance with EN 14566:2008 "Screw for plasterboard".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 12 May 2021

Hieu Trong Nguyen

SWISSTEC Sourcing Ltd.



Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM011712-136

Item No: 500978420

Description:

3000pcs Drywall screw trim head phillip drive coarse, reverse thread blue plated in square tub - 3.8x35

Material: C1022

Certificate No.: [J-32-20199-18](#)

Report No.: [32-9996/2](#)

| Description | Nominal diameter (mm) | Inner thread diameter (mm) | Head diameter (mm) | Total length (mm) | Thread length (mm) | Tensile strength in bending (15°) | Withdrawal strength (N) | Headpull-through strength (N) | Drilling ability (s) | Protective layer (24H) |
|-------------|--------------------------|-------------------------------|-----------------------|----------------------|-----------------------|--------------------------------------|----------------------------|----------------------------------|-------------------------|---------------------------|
| 3.8x35 | 3.6 - 3.9 | 2.35 - 2.65 | 6.5 - 7.0 | 33.7 - 36.3 | Full | Pass | 810 - 958 | 290 - 350 | 0.20 - 0.42 | Pass |

The manufacturer declares for:

The product is in accordance with EN 14566:2008 "Screw for plasterboard".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 29 Aug 2020



Hieu Trong Nguyen

SWISSTEC Sourcing Ltd.



Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM011712-136

Item No: 500978420

Description:

3000pcs Drywall screw trim head phillip drive coarse, reverse thread blue plated in square tub - 3.8x35

Material: Carbon steel C1022

Certificate No.: [J-32-20199-18](#)

Report No.: [32-9996/2](#)

| Description | Nominal diameter (mm) | Inner thread diameter (mm) | Head diameter (mm) | Total length (mm) | Thread length (mm) | Tensile strength in bending (15°) | Withdrawal strength (N) | Headpull-through strength (N) | Drilling ability (s) | Protective layer (24H) |
|-------------|--------------------------|-------------------------------|-----------------------|----------------------|-----------------------|--------------------------------------|----------------------------|----------------------------------|-------------------------|---------------------------|
| 3.8x35 | 3.6 - 3.9 | 2.35 - 2.65 | 6.5 - 7.0 | 33.7 - 36.3 | Full | Pass | 817 - 910 | 290 - 348 | 0.20 - 0.42 | Pass |

The manufacturer declares for:

The product is in accordance with EN 14566:2008 "Screw for plasterboard".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 17 Apr 2019



Hieu Trong Nguyen